VIBRATION RANGE

i-SPYDER

Integrated electronic converter

The SPYDER is a plug and play integrated electronic converter that powers a high frequency vibrator. The range consists of the SPYDER PRO and the i-SPYDER.







Converter and poker No integrated in a required. No waste ready-to-use kit.



Zero maintenance

spare generation or periodic used in places of maintenance needs.



Light and compact

Lightweight manageable, can be difficult access and handled by a single operator.



Safe and reliable

Hermetic protective housing that protects it against water and dust (IP67). Electrical protection against overloads, overvoltage, short circuits...

- Converter weight: 3.4kg
- Vibration frequency 12,000 v.p.m.
- Optional rubber poker end
- Standard voltage/frequency input: 230v~50/60Hz (Optionally available in 110v~50/60Hz, upon request)
- Standard lengths: 5m transmission and 15m cable (other lengths available)
- Progressive start to avoid current peaks, preventing deterioration
- Tricolor external LED indicator to communicate any incident to the user (For i-Spyder Button)
- Optional PRCD protection system that immediately disconnects the machine if there is a current leakage of 10mA





Technical Data

| MODEL | Total weight | Length | Diameter | Power of input | Performance |
|------------------|-----------------|--------|----------|----------------|-------------|
| MODEL | (kg) | (mm) | (mm) | (KW) | (m3/h) |
| i-SPYDER 230V-30 | 11.5 | 353 | 30 | 0.4 | Up to 10 |
| i-SPYDER 230V-38 | 13 | 370 | 38 | 0.75 | Up to 20 |
| i-SPYDER 230V-50 | 17 | 365 | 50 | 1.1 | Up to 30 |
| i-SPYDER 230V-60 | 19 | 400 | 58 | 1.5 | Up to 35 |
| i-SPYDER 230V-70 | 20 | 400 | 65 | 1.9 | Up to 40 |

*All the i-SPYDERs are available both in Switch version and Button version.