


**COMPACTION RANGE**

# DEEP

## Tamping rammers

The DEEP range offers the user manageable, reliable, and easily transportable tamping rammers.



**+ Air filter**

DEEP rammers have a 3-stage filter that progressively retains particles according to their size.



**+ Noise reduction**

The fuel tank, located on the handlebar, serves as a barrier, such as acoustic shielding, to reduce the noise that reaches the user.



**+ Economic maintenance**

Designed for low maintenance cost with cost-controlled wear items.



**+ Comfortable**

Compensated and balanced jump for a more comfortable use of the machine by the user.

- The DEEP rammers range offers different models between 65 and 80kg
- Different diesel and petrol engines
- Dimensions : 770x398x1038 mm / Foot dimensions: 332x280 mm
- Number of hits per minute: 650 v.p.m.
- Optional air filter saturation sensor
- Tachometer with optional operating hours and engine revolutions indicator
- Large 3-stage air filter



### Technical Data

MODEL	Weight without fuel (kg)	Elevation (mm)	Impact force (Kg)	Engine	Speed (r.p.m.)	Power (CV)	Performance (m2)	Fuel
PH 70E	73	70	1540	HONDA GXR120RT KR EE	3700	4	210	Petrol
PH 70LC	74	70	1540	ENAR G165F 4 CV	3700	3.5	210	Petrol
PH 80YD	81	70	1510	YANMAR L 48 AE	3650	4.1	205	Diesel