COMPACTION RANGE

ZEN

Forward plate compactors

ZEN forward plate compactors are manageable and easy to transport thanks to their integrated wheels.













Simple transport

Plate Compactors made of high resistanincorporates ce cast iron. In machine.

Sturdiness

The range of ZEN The base of the ZEN is protects the motor.

Complete range

compactors transport wheels to addition, it incorpora- different motoriza- system, facilitate moving the tes a cage that tions that adapt to work. each client.

Ergonomics and comfort

Complete range of Integrated handle that unidirectional plate folds and incorporates a with vibration absorption facilitating

- Easy start-up through a centrifugal clutch
 - Different manufacturers petrol and/or diesel engines options
- Vibration frequency: 5,600 vib/min
- Optional polyurethane sheet for paving stone compaction
- Recommended for working on asphalt
- Optional 9L water tank provided with quick assembly and disassembly system for easy filling





Technical Data

MODEL	Weight without fuel (kg)	Centrifugal force (N)	Speed (m/min)	Dimensions (WidexLargexHigh)	Plate length (mm)	Engine
ZEN 16CGH/CGL	90	16,000	0-22	400x1165x958	414	
ZEN 16DGH/DGL	94	16,000	0-22	500x1165x958	414	HONDA GX 160
ZEN 20CGH/CGL	91	20,000	0-24	400x1165x958	414	ENAR G200 F
ZEN 20DGH/DGL	95	20,000	0-24	500x1165x958	414	
ZEN 16CDH	106	16,000	0-22	400x1168x1015	414	
ZEN 16DDH	110	16,000	0-22	500x1168x1015	414	HATZ 1B 20
ZEN 20CDH	107	20,000	0-24	400x1168x1015	414	11/1/2 18 20
ZEN 20DDH	111	20,000	0-24	500x1168x1015	414	