

VIBRATION RANGE

ANE

Pendulum pokers and transmissions

The ANE range has a wide variety of pokers and transmissions, with various couplings.



- High quality transmission
- Extra protection where the transmission attaches to the poker
- Standard coupling: Dynapac. For different types of pins, please consult us.
- Axis rotation frequency: 3.000 r.p.m. Poker vibration frequency: 12.000 v.p.m.
- Transmission diameter: 16/30mm for ANE28, ANE38 and ANE45, & 20/36mm for ANE50, ANE60 and ANE70.



Technical Data ANE Pokers


| MODEL | Poker weight (kg) | Poker length (mm) | Poker diameter (mm) | Speed (v.p.m.) | Amplitude (mm) | Transmission length* (m) |
|--------|-------------------|-------------------|---------------------|----------------|----------------|--------------------------|
| ANE 25 | 1.76 | 560 | 25 | 15,000 | 1.2 | 6 |
| ANE 38 | 3.2 | 595 | 38 | 12,000 | 1.4 | 6 |
| ANE 45 | 4.08 | 595 | 45 | 12,000 | 1.6 | 6 |
| ANE 50 | 4.94 | 560 | 50 | 11,000 | 1.8 | 6 |
| ANE 60 | 6.02 | 595 | 60 | 11,000 | 2.4 | 6 |
| ANE 70 | 8.12 | 570 | 70 | 11,000 | 2.6 | 6 |

*Other transmission lengths available upon request.



+ Adaptability

The ANE range adapts to all types of works, thanks to its indistinct operation with electric, petrol or diesel motors.



+ Versatility

Wide range of diameters and couplings adapt to all types of users.



+ Resistance

The greatest stress area is rubber reinforced. Robust mechanical system.