

VIBRATION RANGE

ANR/TNR

Pendulum pokers and transmissions

The ANR/TNR range has a wide variety of pokers and transmissions, with various couplings.




- High quality transmission
- Extra protected Transmission where the transmission attaches to the poker (For 48, 58 and 70mm models)
- For different types of pins, please consult
- Axis rotation frequency: 3.000 r.p.m. Poker vibration frequency: 12.000 v.p.m.
- Transmission diameter: 26mm for ANR25 poker and 36mm for the others



+ Adaptability

The TNR/ANR range adapts to all types of works, thanks to its indistinct operation with electric, petrol or diesel motors.



+ Versatility

Wide range of diameters and couplings adapt to all types of users.



+ Resistance

The greatest stress area is rubber reinforced. Robust mechanical system.

Technical Data ANR/TNR

MODEL	Total weight (kg)	Poker length (mm)	Poker diameter (mm)	Speed (r.p.m.)	Max. performance (m ³ /h)	Transmission length* (m)
TNR 6-25 + ANR 25	9,2	350	25	17,000	10	6
TNR 6-38 + ANR 38	18,3	375	38	12,000	15	6
TNR 6-48 + ANR 48	19,3	445	48	12,000	25	6
TNR 6-58 + ANR 58	21,8	450	58	12,000	32	6
TNR 6-70 + ANR 70	23,3	510	70	12,000	35	6

*Standard transmission length: 6 metres. For other lengths, please consult us.