

VIBRATION RANGE

ANR/TNR

Pendulum pokers and transmissions

The ANR/TNR range has a wide variety of pokers and transmissions, with various couplings.



- High quality transmission
- Extra protected Transmission where the transmission attaches to the poker (For 48, 58 and 70mm models)
- For different types of pins, please consult
- Axis rotation frequency: 3.000 r.p.m. Poker vibration frequency: 12.000 v.p.m.
- Transmission diameter: 26mm for ANR25 poker and 36mm for the others



Technical Data ANR Pokers

MODEL	Weight (kg)	Length (mm)	Diameter (mm)	Speed (r.p.m.)	Performance (m3/h)	Transmission
ANR 25	1.2	350	25	16,000	10	TNR4-25/TNR6-25
ANR 38	2.5	375	38	12,000	15	TNR4-38/TNR6-38
ANR 48	4.3	445	48	12,000	25	TNR4-48/TNR6-48
ANR 58	6.4	450	58	12,000	30	TNR4-58/TNR6-58
ANR 70	7.5	510	70	12,000	35	TNR4-70/TNR6-70


Technical Data TNR Transmissions

MODEL	Weight (kg)	Length (mm)
TNR6- 25	8	6
TNR6- 38	15.8	6
TNR6- 48	15.8	6
TNR6- 58	15.8	6
TNR6- 70	15.8	6



+ Adaptability

The TNR/ANR range adapts to all types of works, thanks to its indistinct operation with electric, petrol or diesel motors.



+ Versatility

Wide range of diameters and couplings adapt to all types of users.



+ Resistance

The greatest stress area is rubber reinforced. Robust mechanical system.